

PDI-772HE
High Efficiency
AC Central Power Supply

General Specification

1. POWER		
	Input	
	Multi-Voltage	No
	Voltage	120 VAC Maximum
	Frequency	60 Hz
	Current	10 A
	Power	950 Watts
	Protection	
	Type	Circuit Breaker
	Style	Thermal, Plunger, Resettable
	Rating	10A
	Faraday Shield	Yes
	Line Filter	Yes
	Power Switch	None
	Line Cord	
	Length	10 feet
	Type	SJT
	Detachable	Yes
	Wire Size	16 Ga
	Plug	
	Type	NEMA 5-15P, Hospital Grade, Straight
	Rating	125V, 15A
	Connector	IEC 60320/C13
	Output	
	Quantity	10
	Multi-Voltage	Yes
	Voltage	28VAC, 32VAC
	Frequency	60 Hz
	Current	3 Amps
	Classification	NEC Class II Level @ 28VAC
	Connector	
	Type	F, Female
	Body	Zinc Cast
	Pin	
	Style	Round Seizing
	Material	Beryllium Copper
	Insulator	PE
	Circuit Protection	
	Type	Circuit Breaker
	Style	Thermal, Plunger, Resettable
	Rating	3.3A
	Impedance Protection	PTC
	Waste Heat	110 Watts @ Full Rating
	Efficiency	89% (Calculated)
	Cooling	
	Fan	No
	Convection	Yes
2. RF PERFORMANCE		
	Bandpass	10 to 1000 Mhz

PDI-772HE
High Efficiency
AC Central Power Supply

	Insertion Loss	14 dbmv
	Return Loss	
	Input	14 dbmv
	Output	16 dbmv
	Isolation	
	Port to Port	20 dbmv Minimum
3. REGULATION		
	Safety	UL, cUL
	FCC	None
	DHHS	N/A
4. PHYSICAL		
	Cabinet	
	Dimensions	10"W x 14.75"L x 7"H
	Mounting	¼ x 20 Hardware
	Weight	28 lbs.
	Cooling	Convection
	Operational Temp Range	20-50 °C
	Cable Access Cover	Yes, Removable

